

# Texecom

## NEW PRODUCT SUMMARY

### motion detectors



Tamper-proof Wall & Ceiling Brackets



3 LED Indication



Interchangeable Chassis

#### *Prestige IR*

High immunity 15m range PIR with interchangeable electronics module. Multi-mode digital pulse count maximises detector performance.



#### *Prestige QD*

Quad element 15m range digital PIR with interchangeable electronics module. Genuine quad detection with 3 LED indication provides additional stability for harsh environments.



#### *Prestige TD*

Twin dual element 15m range digital PIR with interchangeable electronics module. Two dual element sensors provide exceptional stability, ideal for commercial applications.



#### *Prestige DT*

Digital dual technology 15m range detector with interchangeable electronics module. X-band doppler, adjustable microwave range, digital temperature compensation & advanced signal processing ensures maximum false alarm immunity. CloakWise™ (CW) version also available.



#### *Prestige MR*

Digital 15m range PIR with mirrored optics. Adjustable mounting height, sealed mirrored optics & digital temperature compensation guarantee exceptional catch performance.



#### *Prestige Compact IR*

Miniature cost effective 15m range PIR with sealed optics. Surface mount signal processing ensures excellent reliability. Complete with 2-piece wall & ceiling bracket.



### heat & smoke detectors



Aesthetic Design




High Visibility LED Indication

#### *Exodus OH/4W*

Optical & heat multisensor with built-in 12V relay for 4-wire connection to security control panels. Heat enhancement ensures high sensitivity to fast burning fires whilst optical chamber provides exceptional false alarm immunity.


**Example Usage: optimum protection for fastest fire detection.**



#### *Exodus RR/4W*

Rate of rise heat detector with built-in 12V relay for 4-wire connection to security control panels. Suitable for use where smoke or dust is prevalent with fastest heat detection performance.


**Example Usage: bars & public places.**



#### *Exodus FT64/4W*

Fixed 64°C heat detector with built-in 12V relay for 4-wire connection to security control panels. Suitable for use where smoke or dust is prevalent with superior false alarm immunity.


**Example Usage: bathrooms & kitchens.**



#### *Exodus FT90/4W*

Fixed 90°C heat detector with built-in 12V relay for 4-wire connection to security control panels. Suitable for use where smoke or dust is prevalent, ideal for extreme high ambient temperatures.

**Example Usage: boiler rooms.**



## perimeter protection



Glass Break LED Indication & Microphone Cover Cap

### *Impaq Glass Break*

Advanced digital acoustic glassbreak detector. Quad real time frequency analysis coupled with digital flex detection ensure outstanding performance for plate, tempered, laminated & wired glass types.



## control panels & accessories



Range of Keypads Available

### *Premier 24*


8 zone control panel expandable to 24 with the addition of *Premier 8XP/8XE/4XP* zone expanders and LCD keypads. Up to 4 keypads, 16 user codes, 500 event log, facility for plug-on multi-protocol digimodem with local & remote upload/download via *Wintex* software.



Proximity Keypad & Tag


### *Premier 832*

International 8 zone control panel expandable to 32 with the addition of *Premier 8X/8XE* zone expanders. Up to 6 LED/LCD keypads, 4 true areas, 32 user codes, 750 event log, integrated digital communicator/modem, local & remote upload/download via *Wintex* software.



### *Premier LCDP/LCDLP*

LCD keypads with built-in proximity tag reader. Featuring 32 character display, 2 fully programmable DP or EOL zones, fully programmable output, adjustable backlighting & built-in piezo sounder. *LCDLP* includes large screen display & additional speaker driver output.



Backlit Touch Tone Keys

### **Texecom** *Speech Dialler*

*Speech Dialler* featuring 4 trigger inputs, 4 voice messages - each up to 32 seconds long, 8 contact numbers, call acknowledgement, call abort, 4 programmable outputs, listen-in mode, talkback mode, memo feature, remote access & context sensitive help. Additional 4 text messages - each up to 32 characters long - provided with *Texecom Speech & Text Dialler*.



## external sounders



360° Strobe

### *Odyssey 4*

360° external sounder & strobe unit. 115dB at 1m, IP65 sealed electronics, unique patented engineer hold-off mode & advanced microprocessor technology. Polycarbonate construction with screw, lid & wall tamper detection.



### *Odyssey 4E*

360° external sounder & strobe unit. 109dB at 1m, unique patented engineer hold-off mode & advanced microprocessor technology. Polycarbonate construction with lid & wall tamper detection.

